



Rx 34.0 E

Thermoplastic, firm to hard counter material that is covered on both sides with a hydrophobic polyester fabric. The material can be easily processed and enables highly reliable bonding to almost all known upper materials. Because the adhesive is in the compound, even the skived edges are sticky. The material can be used e.g. for ladies' and men's shoes, and in lower thicknesses for children's shoes etc..




MATERIAL DATA


Material thickness



Material hardness



Adhesive



Types

Rx 3420 E
Rx 3430 E
Rx 3450 E
Rx 3460 E

Thickness

1.00 - 1.15 mm
1.10 - 1.25 mm
1.40 - 1.55 mm
1.50 - 1.65 mm

Processing HOT/COLD

90°C - 100°C
Interface temperature

130°C - 140°C
Activating temperature

20 - 30 seconds

Delivery

Sheets, 1.00 x 1.50 m

Cutting

↑ Length direction

Manufacturers warranty: Due to the great number of materials being used for shoe manufacturing the possibilities of chemical reactions and incompatibilities between components should be always tested beforehand. We are not liable for damages arising by non observance of our instructions for applications or from reactions beyond our influence and control.

Storing: Under normal conditions the storage is unlimited. Avoid direct storing in the sun. We guarantee for the goods 6 month after delivery date.

Rhenoflex GmbH
Giulinistrasse 2
67065 Ludwigshafen am Rhein
Germany

Customer Service
p +49 621 5709 - 6732
w rhenoflex.com
e support@rhenoflex.com

Managing Director:
Frank Böttcher
Registered office:
Ludwigshafen am Rhein
VAT No.:
DE815544462

SWIFT:
COBADEFFXXX
Jurisdiction/
Court of registration:
Amtsgericht Ludwigshafen
HRB 64276

Version 2.0/1

