


Pyroflex 512 SE


Tear proof reinforcement material with less extension on cotton fabric base.

MATERIAL DATA

Material thickness



Material hardness



Adhesive




Types

Pyroflex 512 SE


Weight


124 g/m²

Processing

 120°C - 140°C
 Activating temperature

Delivery

 Colors

 4 - 8 seconds

Manufacturers warranty: Due to the great number of materials being used for shoe manufacturing the possibilities of chemical reactions and incompatibilities between components should be always tested beforehand. We are not liable for damages arising by non observance of our instructions for applications or from reactions beyond our influence and control.

Storing: Under normal conditions the storage is unlimited. Avoid direct storing in the sun. We guarantee for the goods 6 month after delivery date.

Rhnoflex GmbH
 Giulinistrasse 2
 67065 Ludwigshafen am Rhein
 Germany

Customer Service
 p +49 621 5709 - 6732
 w rhnoflex.com
 e support@rhnoflex.com

Managing Director:
 Frank Böttcher
 Registered office:
 Ludwigshafen am Rhein
 VAT No.:
 DE815544462

SWIFT:
 COBADEFFXXX
 Jurisdiction/
 Court of registration:
 Amtsgericht Ludwigshafen
 HRB 64276

Version 1.9/1

