


# Pyroflex 513 SE


Tear proof reinforcement material with less extension on cotton fabric base.

## MATERIAL DATA

### Material thickness



### Material hardness



### Adhesive

 One side /  
EVA


### Types

Pyroflex 513 SE

### Weight


94 g/m<sup>2</sup>

### Processing

 120°C - 140°C  
Activating temperature

### Delivery

 Colors

 4 - 8 seconds

**Manufacturers warranty:** Due to the great number of materials being used for shoe manufacturing the possibilities of chemical reactions and incompatibilities between components should be always tested beforehand. We are not liable for damages arising by non observance of our instructions for applications or from reactions beyond our influence and control.

**Storing:** Under normal conditions the storage is unlimited. Avoid direct storing in the sun. We guarantee for the goods 6 month after delivery date.

**Rhenoflex GmbH**  
Giuliniinstrasse 2  
67065 Ludwigshafen am Rhein  
Germany

**Customer Service**  
p +49 621 5709 - 6732  
w rhenoflex.com  
e support@rhenoflex.com

**Managing Director:**  
Frank Böttcher  
Registered office:  
Ludwigshafen am Rhein  
VAT No.:  
DE815544462

**SWIFT:**  
COBADEFFXXX  
Jurisdiction/  
Court of registration:  
Amtsgericht Ludwigshafen  
HRB 64276

Version 1.9/1

